



Part Number	Pin Diameter D
360P12Y2	0.30mm / 0.012"
360P20Y2	0.51mm / 0.020"

Specifications:

Impedance= 50 Ω
 Frequency= DC - 40 Ghz
 VSWR : DC - 40 Ghz = 1.15:1 max
 Contact Resistance: Center Contact ≤ 3.0 mΩ
 Contact Resistance: Housing ≤ 2 .0 mΩ
 Insulation Resistance ≥ 3000 MΩ
 Dielectric Withstanding Voltage = 750 V
 Durability = 500 cycles
 Temperature Range= -55 °C - +165 °C
 Interfaces: **PER MIL-STD-348A**

Material / Finish

Housing: Stainless Steel SU303 Polished / Passivated
 Center Contact: Beryllium Copper Gold plated (MIL-G-45204)
 Insulators: PTFE and PEI

SigaTek

423 Black Oak Ridge Rd.
 Wayne, NJ 07470
 Ph: 973-706-8475, Fax: 973-832-4435
 www.sigatek.com

360P12Y2
 360P20Y2

2.92mm Female Connectors

Dimensions are in inches and (mm)
 Decimal Tolerance:
 2 place +- 0.020
 3 place +- 0.010

CAGE CODE : 69UC1

Notes: All dimensions are typical unless they are specified.
 Specifications are subject to change at any time without any notice.
 Copy or distribution of this drawing is not allowed without Sigatek's approval.