



N Male DC-18 Ghz

Part Number	Socket Diameter
341P20F9	0.51mm-20 mils
341P36F9	0.91mm-36 mils

Specifications:

Impedance= 50 Ω
 Frequency= DC - 18 Ghz
 VSWR : DC - 18 Ghz = 1.15:1 max
 Contact Resistance: Center Contact \leq 1.0 m Ω
 Contact Resistance: Housing \leq 0.2 m Ω
 Insulation Resistance \geq 5000 M Ω
 Dielectric Withstanding Voltage = 1500 V
 Durability = 500 cycles
 Temperature Range= -55 $^{\circ}$ C - +165 $^{\circ}$ C
 Interfaces: **PER MIL-STD-348A**

Material / Finish

Housing: Stainless Steel SU303 Polished / Passivated
 Center Contact: Beryllium Copper Gold plated (MIL-G-45204)
 Insulators: PTFE and PEI

SigaTek

423 Black Oak Ridge Rd.
 Wayne, NJ 07470
 Ph: 973-706-8475, Fax: 973-832-435
 www.sigatek.com

341PxxF9

Coaxial Connector 50 ohm
 N Male

Dimensions are in inches and (mm)
 Decimal Tolerance:
 2 place +- 0.020
 3 place +- 0.010
 mm (mils)

CAGE CODE : 69UC1

Notes: All dimensions are typical unless they are specified.
 Specifications are subject to change at any time without any notice.
 Copy or distribution of this drawing in not allowed without Sigatek's approval.