



### 2.92 Female DC-40 Ghz

Part Number	Socket Diameter
360P09F4	0.23mm-09 mils
360P12F4	0.30mm-12 mils
360P20F4	0.51mm-20 mils

#### **Specifications:**

Impedance= 50 Ω  
 Frequency= DC - 40 Ghz  
 VSWR : DC - 40 Ghz = 1.15:1 max  
 Contact Resistance: Center Contact ≤ 3.0 mΩ  
 Contact Resistance: Housing ≤ 2.0 mΩ  
 Insulation Resistance ≥ 3000 MΩ  
 Dielectric Withstanding Voltage = 750 V  
 Durability = 500 cycles  
 Temperature Range= -55 °C - +165 °C  
 Interfaces: **PER MIL-STD-348A**

#### **Material / Finish**

Housing: Stainless Steel SU303 Polished / Passivated  
 Center Contact: Beryllium Copper Gold plated (MIL-G-45204)  
 Insulators: PTFE and PEI

# SigaTek

423 Black Oak Ridge Rd.  
 Wayne, NJ 07470  
 Ph: 973-706-8475, Fax: 973-832-435  
 www.sigatek.com

## 360PxxF4

Coaxial Connector 50 ohm  
 2.92mm Female

Dimensions are in inches and (mm)  
 Decimal Tolerance:  
 2 place +- 0.020  
 3 place +- 0.010  
 mm (mils)

**CAGE CODE : 69UC1**

Notes: All dimensions are typical unless they are specified.  
 Specifications are subject to change at any time without any notice.  
 Copy or distribution of this drawing is not allowed without Sigatek's approval.