



2.4mm Male DC-50 Ghz

Part Number	Socket Diameter
371P09F4	0.23mm-09 mils
371P12F4	0.30mm-12 mils
371P20F4	0.51mm-20 mils

Specifications:

Impedance= 50 Ω
 Frequency= DC - 50 Ghz
 VSWR : DC - 50 Ghz = 1.15:1 max
 Contact Resistance: Center Contact \leq 3.0 m Ω
 Contact Resistance: Housing \leq 2 .0 m Ω
 Insulation Resistance \geq 3000 M Ω
 Dielectric Withstanding Voltage = 750 V
 Durability = 500 cycles
 Temperature Range= -55 $^{\circ}$ C - +165 $^{\circ}$ C
 Interfaces: **PER IEEE STD 287-2007**

Material / Finish

Housing: Stainless Steel SU303 Polished / Passivated
 Center Contact: Beryllium Copper Gold plated (MIL-G-45204)
 Insulators: PEI or PTFE and PEI

SigaTek

423 Black Oak Ridge Rd.
 Wayne, NJ 07470
 Ph: 973-706-8475, Fax: 973-832-435
www.sigatek.com

371PxxF4

Coaxial Connector 50 ohm
 2.4mm Male

Dimensions are in inches and (mm)
 Decimal Tolerance:
 2 place +- 0.020
 3 place +- 0.010
 mm (mils)

CAGE CODE : 69UC1

Notes: All dimensions are typical unless they are specified.
 Specifications are subject to change at any time without any notice.
 Copy or distribution of this drawing in not allowed without Sigatek's approval.