



1.85mm Female DC-65 Ghz

Part Number	Socket Diameter
380P09F1	0.23mm-09 mils
380P12F1	0.30mm-12 mils

Specifications:

Impedance= 50 Ω
 Frequency= DC - 65 Ghz
 VSWR : DC - 65 Ghz = 1.25:1 max
 Contact Resistance: Center Contact ≤ 3.0 mΩ
 Contact Resistance: Housing ≤ 2.5 mΩ
 Insulation Resistance ≥ 3000 MΩ
 Dielectric Withstanding Voltage = 500 V
 Durability = 500 cycles
 Temperature Range= -55 °C - +165 °C
 Interfaces: **PER IEC - 61169**

Material / Finish

Housing: Stainless Steel SU303 Polished / Passivated
 Center Contact: Beryllium Copper Gold plated (MIL-G-45204)
 Insulators: PEI

SigaTek

423 Black Oak Ridge Rd.
 Wayne, NJ 07470
 Ph: 973-706-8475, Fax: 973-832-435
 www.sigatek.com

380PxxF1

Coaxial Connector 50 ohm
 1.85mm Female

Dimensions are in inches and (mm)
 Decimal Tolerance:
 2 place +- 0.020
 3 place +- 0.010
 mm (mils)

CAGE CODE : 69UC1

Notes: All dimensions are typical unless they are specified.
 Specifications are subject to change at any time without any notice.
 Copy or distribution of this drawing in not allowed without Sigatek's approval.