



### SMA Female DC-27 Ghz

Part Number	Socket Diameter
550P09F5	0.23mm-09 mils
550P12F5	0.30mm-12 mils
550P20F5	0.51mm-20 mils

- **Specifications:**
- Impedance= 50 ohms
- Frequency= DC – 27 Ghz
- Durability = 500 cycles
- Temperature Range= -55 C - +165 C
- Interfaces: PER MIL-STD 348A
- VSWR 1.15 Max DC-27 Ghz
- **Material / Finish**
- Housing: Stainless Steel SU303 Polished / Passivated
- Center Contact: Beryllium Copper Gold plated (MIL-G-45204)
- Insulators: PTFE & PEI

# SigaTek

423 Black Oak Ridge Rd.  
Wayne, NJ 07470  
Ph: 973-706-8475, Fax: 973-832-435  
www.sigatek.com

## 550PxxF5

Coaxial Connector 50 ohm  
SMA Female

Dimensions are in inches and (mm)  
Decimal Tolerance:  
2 place +- 0.020  
3 place +- 0.010  
mm (mils)

**CAGE CODE : 69UC1**

Notes: All dimensions are typical unless they are specified.  
Specifications are subject to change at any time without any notice.  
Copy or distribution of this drawing in not allowed without Sigatek's approval.