



Part Number	D1	D2	L1	L2
550P103F4	2.2mm-87mils	0.3mm-12mils	3.2mm-126mils	1.27mm-50mils
550P203F4	2.2mm-87mils	0.3mm-12mils	4.2mm-165mils	1.27mm-50mils

• **Specifications:**

- Impedance= 50 ohms
- Frequency= DC – 27 Ghz
- Durability = 500 cycles
- Temperature Range= -55 C - +165 C
- Interfaces: PER MIL-STD 348A
- VSWR 1.15 Max DC-27 Ghz

• **Material / Finish**

- Housing: Stainless Steel SU303 Polished / Passivated
- Center Contact: Beryllium Copper Gold plated (MIL-G-45204)
- Insulators: PTFE & PEI

SigaTek

423 Black Oak Ridge Rd.
Wayne, NJ 07470
Ph: 973-706-8475, Fax: 973-832-435
www.sigatek.com

550PxxxF4

**SMA with Extended
Teflon PTFE**

Dimensions are in inches and (mm)
Decimal Tolerance:
2 place +- 0.020
3 place +- 0.010

CAGE CODE : 69UC1

Notes: All dimensions are typical unless they are specified.
Specifications are subject to change at any time without any notice.
Copy or distribution of this drawing in not allowed without Sigatek's approval.