



### SMA Male DC-27 Ghz

Part Number	Socket Diameter
551P09F4	0.23mm-09 mils
551P12F4	0.30mm-12 mils
551P20F4	0.51mm-20 mils

- **Specifications:**
- Impedance= 50 ohms
- Frequency= DC – 27 Ghz
- Durability = 500 cycles
- Temperature Range= -55 C - +165 C
- Interfaces: PER MIL-STD 348A
- VSWR 1.15 Max DC-27 Ghz
- **Material / Finish**
- Housing: Stainless Steel SU303 Polished / Passivated
- Center Contact: Beryllium Copper Gold plated (MIL-G-45204)
- Insulators: PTFE & PEI

# SigaTek

423 Black Oak Ridge Rd.  
Wayne, NJ 07470  
Ph: 973-706-8475, Fax: 973-832-435  
www.sigatek.com

## 551PxxF4

Coaxial Connector 50 ohm  
SMA Male

Dimensions are in inches and (mm)  
Decimal Tolerance:  
2 place +- 0.020  
3 place +- 0.010  
mm (mils)

**CAGE CODE : 69UC1**

Notes: All dimensions are typical unless they are specified.  
Specifications are subject to change at any time without any notice.  
Copy or distribution of this drawing in not allowed without Sigatek's approval.