



Electrical Specifications:

Frequency Range:	RFin to RF+LF	1.0 – 18.0	Ghz	
Insertion Loss:	RFin to RF+LF	1.5	dB	Max
Isolation:	RFin to LF port	40	dB	Min
VSWR:	RFin, RF+LF ports	1.70:1	--	Max

Frequency Range:	LF to RF+LF	DC – 200	Mhz	
Insertion Loss:	LF to RF+LF	1.5	dB	Max
VSWR:	LF port	2.00:1	--	Max

Current Amps:	0.5	Amp	Max
Vdc:	50	Vdc	Max
Input Power RFin:	1.0	Watts	Max

Connectors - Ports: SMA Female
 Operating Humidity: Up to 95% Non-condensing
 Operating Temperature: -55 °C to 80°C
 Housing material: Aluminum 6061-T6
 Finish: Nickel plating

SigaTek

423 Black Oak Ridge Rd.
 Wayne, NJ 07470
 Ph: 973-706-8475, Fax: 973-832-4435
 www.sigatek.com

SBD13D2

**Diplexer - Bias Tee
 SMA Connectors**

Dimensions are in inches and (mm)
 Decimal Tolerance:
 2 place +- 0.020
 3 place +- 0.010

CAGE CODE : 69UC1

Notes: All dimensions are typical unless they are specified.
 Specifications are subject to change at any time without any notice.
 Copy or distribution of this drawing is not allowed without Sigatek's approval.