	Ref. 92mm emale 10.7 (.421 <sup>*</sup> ) (1.09	9.6 (.378°)	A 4P T DIA (625° DIA) (000° J (000° J (12.7) (.500° SQ)
<ul> <li><u>Specifications:</u></li> <li>Impedance= 50 ohms</li> <li>Frequency= DC - 40 Ghz</li> <li>Durability = 500 cycles</li> </ul>		SigaTek	423 Black Oak Ridge Rd. Wayne, NJ 07470 Ph: 973-706-8475, Fax: 973-832-435 www.sigatek.com
<ul> <li>Temperature Range= -55 C - +165 C</li> <li>VSWR 1.20 Max DC-40 Ghz</li> <li><u>Marerial / Finish</u></li> <li>Housing: Stainless Steel SU303 Polished / Passivated</li> <li>Center Condact: Beryllium Copper Gold plated (MIL-G-45204)</li> <li>Insulators: PEI</li> <li>2.92mm Interfaces PER MIL-STD-348A</li> </ul>		SA113	Adapter Panel Mount 2.92mmFemale-2.92mmFemale
		Dimensions are in inches and (mm) Decimal Tolerance: 2 place +- 0.020 3 place +- 0.010	CAGE CODE : 69UC1
		Notes: All dimensions are typical unless they are specified. Specifications are subject to change at any time without any notice. Copy or distribution of this drawing in not allowed without Sigatek's approval.	