



Electrical Specifications:

| | | | |
|---------------------|---------------------------|-----|-----|
| Frequency Range: | 300 – 18000 | Mhz | |
| Insertion Loss: | 1.5 | dB | Max |
| Isolation: | 35 | dB | Min |
| | 30 | dB | Min |
| Current Amps: | 0.5 | Amp | Max |
| VSWR Input: | 1.60:1 | | Max |
| Vdc: | 50 | Vdc | Max |
| Operating Temp. | -25°C to + 80°C | | |
| Operating Humidity: | Up to 95%, Non Condensing | | |
| Port connectors: | SMA Female In/Out DC-Pin | | |
| Finish: | Nickel Plating | | |
| Weight: | 0.70 oz / 20gr Typ | | |

SigaTek

423 Black Oak Ridge Rd.
Wayne, NJ 07470
Ph: 973-706-8475, Fax: 973-832-4435
www.sigatek.com

SB11D2D

Bias Tee
SMA with DC-Pin

Dimensions are in inches and (mm)
Decimal Tolerance:
2 place +- 0.020
3 place +- 0.010

CAGE CODE : 69UC1

Notes: All dimensions are typical unless they are specified.
Specifications are subject to change at any time without any notice.
Copy or distribution of this drawing is not allowed without Sigatek's approval.