



Controlled Logic Table									
Bits	Pin-1	Pin-2	Pin-3	Pin-4	Pin-5	Pin-6	Pin-7	Pin-8	Phase Degree
--	1	1	1	1	1	1	1	1	Ref=0
1	0	1	1	1	1	1	1	1	-1.4
2	1	0	1	1	1	1	1	1	-2.8
3	1	1	0	1	1	1	1	1	-5.6
4	1	1	1	0	1	1	1	1	-11.2
5	1	1	1	1	0	1	1	1	-22.5
6	1	1	1	1	1	0	1	1	-45
7	1	1	1	1	1	1	0	1	-90
8	1	1	1	1	1	1	1	0	-180
Total Phase= 360-LSB= 360-1.4 degree									-358.6

DB15 Connector Pin Control Configuration		
Pin-1 TTL= Low Phase= -1.4	Pin-9	No Connection
Pin-2 TTL= Low Phase= -2.8	Pin-10	No Connection
Pin-3 TTL= Low Phase= -5.6	Pin-11	No Connection
Pin-4 TTL= Low Phase= -11.2	Pin-12	No Connection
Pin-5 TTL= Low Phase= -22.5	Pin-13	+5 Vdc
Pin-6 TTL= Low Phase= -45	Pin-14	-5 Vdc
Pin-7 TTL= Low Phase= -90	Pin-15	Ground
Pin-8 TTL= Low Phase= -180		

Electrical Specifications:

Frequency Center: $F_c = 425 \pm 10\%$ Mhz
 Insertion Loss: 5.0 dB Max
 Amplitude Balance: ± 1.0 dB Typ
 Phase Shift: 360-LSB degree Min
 VSWR In / Out: 1.90:1 Max
 Switching Speed: 500 nsec Typ
 Control Voltage TTL: 8 Bits Low= 0-0.8V High= 2-5V
 Supply Voltages: $+5V \pm 10\%$ | $-5V \pm 10\%$
 Input Power: +30 dBm Max
 Operating Temperature: $-45^\circ\text{C} - +85^\circ\text{C}$
 Connectors In / Out: SMA Female
 Connectors Control: DB15-Male
 Note: Phase for every bit is tuned to $\pm 2\%$ degree of bit phase at F_c .

SigaTek

423 Black Oak Ridge Rd.
 Wayne, NJ 07470
 Ph: 973-706-8475, Fax: 973-832-4435
www.sigatek.com

SFD425D10

Digital Phase Shifter

Dimensions are in inches and (mm)
 Decimal Tolerance:
 2 place ± 0.020
 3 place ± 0.010

CAGE CODE :
69UC1

Rev.

A

Notes: All dimensions are typical unless they are specified.
 Specifications are subject to change at any time without any notice.
 Copy or distribution of this drawing in not allowed without Sigatek's approval.