



Controlled Logic Table

Bits	Pin-1	Pin-2	Pin-3	Pin-4	Pin-5	Pin-6	Pin-7	Pin-8	Phase Degree
--	1	1	1	1	1	1	1	1	Ref=0
1	0	1	1	1	1	1	1	1	-1.4
2	1	0	1	1	1	1	1	1	-2.8
3	1	1	0	1	1	1	1	1	-5.6
4	1	1	1	0	1	1	1	1	-11.2
5	1	1	1	1	0	1	1	1	-22.5
6	1	1	1	1	1	0	1	1	-45
7	1	1	1	1	1	1	0	1	-90
8	1	1	1	1	1	1	1	0	-180
Total Phase= 360-LSB= 360-1.4 degree									-358.6

DB15 Connector Pin Control Configuration

Pin-1 TTL= Low Phase= -1.4	Pin-9 No Connection
Pin-2 TTL= Low Phase= -2.8	Pin-10 No Connection
Pin-3 TTL= Low Phase= -5.6	Pin-11 No Connection
Pin-4 TTL= Low Phase= -11.2	Pin-12 No Connection
Pin-5 TTL= Low Phase= -22.5	Pin-13 +5 Vdc
Pin-6 TTL= Low Phase= -45	Pin-14 -5 Vdc
Pin-7 TTL= Low Phase= -90	Pin-15 Ground
Pin-8 TTL= Low Phase= -180	

Electrical Specifications:

Frequency Center:	Fc= 70±10%	Mhz	
Insertion Loss:	5.0	dB	Max
Amplitude Balance:	±1.0	dB	Typ
Phase Shift:	360-LSB	degree	Min
VSWR In / Out:	1.90:1		Max
Switching Speed:	500	nsec	Typ
Control Voltage TTL	8 Bits Low= 0-0.8V High= 2-5V		
Supply Voltages:	+5V±10% -5V±10%		
Input Power:	+30	dBm	Max
Operating Temperature:	-45°C - +85 °C		
Connectors In / Out:	SMA Female		
Connectors Control:	DB15-Male		
Note:	Phase for every bit is tuned to ±2% degree of bit phase at Fc.		

SigaTek

423 Black Oak Ridge Rd.
Wayne, NJ 07470
Ph: 973-706-8475, Fax: 973-832-4435
www.sigatek.com

SFD70D10

Digital Phase Shifter

Dimensions are in inches and (mm)
Decimal Tolerance:
2 place +- 0.020
3 place +- 0.010

CAGE CODE :
69UC1

Rev.

A

Notes: All dimensions are typical unless they are specified.
Specifications are subject to change at any time without any notice.
Copy or distribution of this drawing in not allowed without Sigatek's approval.