



Electrical:	Specifications:		
Frequency Range:	1.0–2.0	Ghz	Ghz
Insertion Loss:	0.5	dB	Max
Theoretical Loss	3.01	dB	
Amplitude Balance:	±0.6	dB	Max
Isolation:	25	dB	Min
Phase Balance:	±3.0	Deg.	Max
VSWR:	1.20:1		Max
Power Handling Avg:	50	Watt	Max
Power Peak:	1000	Watt	Max
Operating Temp.:	-50 - +85 °C		
Weight:	22	grams	Typ
Operating Humidity:	Up to 95% Non-Condensing		
Input power is rated for load VSWR better than 1.20:1			

<h1>SigaTek</h1>	423 Black Oak Ridge Rd. Wayne, NJ 07470 Ph: 973-706-8475, Fax: 973-832-4435 www.sigatek.com
<h2>SQ11501T</h2>	<h3>Hybrid 3 db 90 degree 1-2 Ghz</h3>
Dimensions are in inches and (mm) Decimal Tolerance: 2 place +- 0.020 3 place +- 0.010	CAGE CODE : 69UC1
Notes: All dimensions are typical unless they are specified. Specifications are subject to change at any time without any notice. Copy or distribution of this drawing in not allowed without Sigatek's approval.	