



Electrical:

Specifications:

| | | | |
|---|--------------------------|-------|-----------|
| Frequency Range: LO | 133-147 | Mhz | |
| Frequency Range: RF | 133-147 | Mhz | |
| Frequency Range: IF | DC-50 | Mhz | |
| LO Power Level: | +10 to +13 | dBm | Typ |
| Conversion Loss: | 8.0 / 9.0 | dB | Typ / Max |
| Side Band Rejection: | 30 | dBc | Min |
| Carrier Rejection: | 30 | dBc | Min |
| Input 1 dB Compression: | +5 | dBm | Typ |
| Low side is Rejected when Q-port is +90 degree relative to I-port | | | |
| Input Two-Tone Third Order Intercept Point: | +15 | dBm | Typ |
| Operating Temp.: | -55 to +80°C | | |
| Weight: | 64 | grams | Typ |
| Operating Humidity: | Up to 90% non-condensing | | |

SigaTek

423 Black Oak Ridge Rd.
Wayne, NJ 07470
Ph: 973-706-8475, Fax: 973-832-4435
www.sigatek.com

QM16A10

I, Q Side Band Modulator SMA Connectors

Dimensions are in inches and (mm)
Decimal Tolerance:
2 place +- 0.020
3 place +- 0.010

CAGE CODE : 69UC1

Notes: All dimensions are typical unless they are specified.
Specifications are subject to change at any time without any notice.
Copy or distribution of this drawing is not allowed without Sigatek's approval.