



Electrical:

Electrical:		Specifications:	
Frequency Range:	2.0 – 18.0	Ghz	
Coupling:	10.0 ± 1.00	dB	
Insertion Loss:	1.00	dB Max	
Coupling Flatness:	± 0.8	dB Max	
Directivity:	12	dB Min	
VSWR:	1.50:1	Max	
Power Forward:	25	Watts	
Power Reflected:	10	Watts	
Power Peak:	3	KW	
Weight:	1.4 / 39.7	Ounces / grams	
Operating Temperature:	-40°C to +85°C		
Input power is rated for load VSWR better than 1.20:1.			
Insertion loss does not include coupling loss.			
Coupling loss for 10 db is 0.456 db			

SigaTek

423 Black Oak Ridge Rd.
Wayne, NJ 07470
Ph: 973-706-8475, Fax: 973-832-4435
www.sigatek.com

SC1017116

Directional Coupler 10 dB

Dimensions are in inches and (mm)
Decimal Tolerance:
2 place +- 0.020
3 place +- 0.010

CAGE CODE : 69UC1

Notes: All dimensions are typical unless they are specified.
Specifications are subject to change at any time without any notice.
Copy or distribution of this drawing is not allowed without Sigatek's approval.
Rev-2= Dimensions 12-23-2020