



Electrical:

| Specifications: | |
|--------------------------------------------------------|---------------------------|
| Frequency Range: | 0.5 – 2.0 Ghz |
| Coupling: | 20.0 ± 1.00 dB |
| Insertion Loss: | 0.35 dB Max |
| Coupling Flatness: | ± 0.75 dB Max |
| Directivity: | 23 dB Min |
| VSWR: | 1.20:1 Max |
| Power Forward: | 50 Watts |
| Power Reflected: | 50 Watts |
| Power Peak: | 3 KW |
| Weight: | 1.6 / 45.4 Ounces / grams |
| Operating Temperature: | -40°C to +85°C |
| Input power is rated for load VSWR better than 1.20:1. | |
| Insertion loss does not include coupling loss. | |
| Coupling is with respect to output. | |

SigaTek

423 Black Oak Ridge Rd.
Wayne, NJ 07470
Ph: 973-706-8475, Fax: 973-832-4435
www.sigatek.com

SC2023109

Directional Coupler 20 dB

Dimensions are in inches and (mm)
Decimal Tolerance:
2 place +- 0.020
3 place +- 0.010

CAGE CODE : 69UC1

Notes: All dimensions are typical unless they are specified.
Specifications are subject to change at any time without any notice.
Copy or distribution of this drawing is not allowed without Sigatek's approval.