



Electrical:

Specifications:

| | | | |
|---|-----------|-----------|-----|
| Frequency Range: | 0.45–7.5 | Ghz | |
| Insertion Loss*: | 3.0 | dB | Typ |
| | 4.0 | dB | Max |
| Amplitude Balance: | 0.8 | dB | Max |
| Isolation: | 20 | dB | Min |
| Phase Balance: | 10 | Deg. | Max |
| VSWR Input: | 1.70:1 | | Max |
| VSWR Output: | 1.70:1 | | Max |
| Power input: | 30 | Watts | Max |
| Connectors: | SMA | | |
| Weight: | 0.837 lbs | 380 grams | |
| *Theoretical loss of 8-way divider is 9.03 dB | | | |
| Input power is rated for load VSWR better than 1.20:1 | | | |

SigaTek

423 Black Oak Ridge Rd.
Wayne, NJ 07470
Ph: 973-706-8475, Fax: 973-832-4435
www.sigatek.com

SP60858

8-way SMA Power Divider

Dimensions are in inches and (mm)
Decimal Tolerance:
2 place +- 0.020
3 place +- 0.010

CAGE CODE : 69UC1

Notes: All dimensions are typical unless they are specified.
Specifications are subject to change at any time without any notice.
Copy or distribution of this drawing is not allowed without Sigatek's approval.